


# Stop & Waste Valves

125 lb. CWP to 100 ° F

Maximum Temperature 180 ° F


CSA B125 Approved and IAPMO Listed



## 75-CL

DESCRIPTION	*NOM. SIZE	DIMENSIONS		APPROX. NET WT.
		A	B	
Stop Valve FIP x FIP	1/2"	2 <sup>3</sup> / <sub>16</sub> "	2 <sup>9</sup> / <sub>16</sub> "	.50 lb
	3/4"	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>9</sup> / <sub>16</sub> "	.60 lb


\*1/4" and 3/8" sizes available, specify figure 75 when ordering



## 725-CL


DESCRIPTION	NOM. SIZE	DIMENSIONS		APPROX. NET WT.
		B	C	
Stop Valve Cup x Cup	1/2"	2 <sup>9</sup> / <sub>16</sub> "	1 <sup>3</sup> / <sub>16</sub> "	.40 lb
	3/4"‡	2 <sup>9</sup> / <sub>16</sub> "	1 <sup>3</sup> / <sub>16</sub> "	.50 lb

\*1/4" and 3/8" sizes available, specify figure 725 when ordering



## 76-CL


DESCRIPTION	NOM. SIZE	DIMENSIONS		APPROX. NET WT.
		A	B	
Stop & Waste Valve FIP x FIP	1/2"	2 <sup>3</sup> / <sub>16</sub> "	2 <sup>9</sup> / <sub>16</sub> "	.54 lb
	3/4"	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>9</sup> / <sub>16</sub> "	.60 lb



## 726-CL, 726-LCL


DESCRIPTION	*NOM. SIZE	DIMENSIONS		APPROX. NET WT.
		B	C	
Stop & Waste Valve Cup x Cup	1/2"	2 <sup>9</sup> / <sub>16</sub> "	1 <sup>3</sup> / <sub>16</sub> "	.42 lb
	3/4"‡	2 <sup>9</sup> / <sub>16</sub> "	1 <sup>3</sup> / <sub>16</sub> "	.49 lb

\*3/8" and 1" sizes available, specify figure 726 when ordering



## 75-CLK

DESCRIPTION	NOM. SIZE	DIMENSIONS		APPROX. NET WT.
		A	B	
Stop & Waste Valve FIP x FIP	1/2"	2 <sup>3</sup> / <sub>16</sub> "	2 <sup>9</sup> / <sub>16</sub> "	.50 lb
	3/4"	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>9</sup> / <sub>16</sub> "	.60 lb



## 75-CLT

DESCRIPTION	*NOM. SIZE	DIMENSIONS		APPROX. NET WT.
		A	B	
Stop & Waste Valve Female Thread	1/2"	2 <sup>3</sup> / <sub>16</sub> "	2 <sup>9</sup> / <sub>16</sub> "	.50 lb

